

The Bush-Whacker T-104

8 Foot Offset Mower

Bush-Whacker mowers from Hall Manufacturing have been popular for decades for highway right-of-way use. Lately, they have been increasingly in demand for agricultural, commercial and other applications where a heavy-duty, rugged mower is needed. The Bush-Whacker is available in a range of sizes to fit your needs — from the five-foot model all the way to the big 20-footer.

Hall Manufacturing has been in business for more than 75 years. During this time they've sold more than 10,000 units and are used in 27 states in the U.S.



- 3 point hitch or pull type
- 3/16" Deck
- Structural frame of mower is 2" by 3" tubing with 1/4" wall thickness
- 1/4" I-Beam sides instead of 1/4" flat steel
- Gearboxes are mounted to 1/2" plates that are welded to the 3/16" deck
- 4 bolt mounting on gearboxes — heads are tack-welded to bottom of deck so one man can tighten the nuts or change the gearbox



Hall Manufacturing

3706 East Washington • P.O. Box 5652 • North Little Rock, AR 72119

PH: 501-945-7550

• www.bush-whacker.com

Model T-104 — 8 Foot Offset Mower

SPECIFICATIONS*

Gearbox — 540 RPM

110 HP main or transfer box, 100 HP outboard boxes with 2 1/8" output shaft, malleable housing, forged alloy steel, carburized and hardened gears and shafts, tapered and ball bearings.

Slip Clutch

Heavy-duty spring type adjustment with two friction discs on main shaft, outboard protection by means of shock absorbing rubber disc connected with splined spiders which form a coupler.

Cutting Width

104" total cut, 57" cutting swathe to right of tractor centerline and 47" to left of tractor centerline.

Shielded PTO and Outboard Shafts — Category 4

Made from finest quality propeller shaft material and needle bearing universal joints.

Blades

1/2" material, alloy spring steel, airlift design, free-swinging for clean cutting, mounted on shoulder bolts.

Two Tail Wheels

For 3 point hitch: Extra heavy-duty, tapered bearings, 4" by 8" laminated puncture-proof tire.

For pull type: Extra heavy-duty, tapered bearings, 6" by 9" laminated puncture-proof tire.

Cutting Height — 2" to 13"

Turner Special Deck — 3/16" Material

Heavy-duty one-piece electric welded frame, rolled I-Beam sides, heavy angle iron and mechanical tubing structurals.

Rolled I-Beam Sides — 1/4" Material

Chain Guards Front and Rear

Heavy-Duty Category One or Two Hitch

Weight — 1,590 lb.

*These specifications are standard; however, any State Department of Transportation Specifications that may differ from standard Bush-Whacker Specifications will take precedence and be implemented into production.

WARRANTY: Guaranteed for 12 months against defective materials and workmanship. Defective parts must be returned prepaid to the factory. Guarantee is void if failure is due to operators negligence, abuse or using other than genuine Bush-Whacker parts.

